



Model	Nominal Voltage (V)	Nominal Current (mA)	Nominal Capacity (mAh)	ContMaximum Continuous Current (mA)	Maximum Pulse Current (mA)	Max Dimension (mm)	Working temperature (°C)	Weight (g)
CR1025	3	0.1	30	1	5	Φ10.0*2.5	-120~+70	0.7
CR1216	3	0.1	25	2	5	φ12.5×1.6	-20~+70	0.7
CR1220	3	0.1	38	2	5	φ12.5×2.0	-20~+70	0.8
CR1225	3	0.1	50	2	5	φ12.5×2.5	-20~+70	0.9
CR1616	3	0.1	50	3	8	φ16.0×1.6	-20~+70	1.2
CR1620	3	0.1	70	3	8	φ16.0×2.0	-20~+70	1.3
CR1632	3	0.1	120	3	8	φ16.0×3.2	-20~+70	2
CR2016	3	0.1	80	5	15	φ20.0×1.6	-20~+70	2
CR2020	3	0.1	120	5	15	φ20.0×2.0	-20~+70	2.2
CR2025	3	0.2	150	5	15	φ20.0×2.5	-20~+70	2.6
CR2032	3	0.2	220	5	15	φ20.0×3.2	-20~+70	3.2
CR2050	3	0.4	330	5	15	φ20.0×5.0	-20~+70	4.7
CR2320	3	0.2	130	6	20	φ23.0×2.0	-20~+70	3
CR2325	3	0.2	190	6	20	φ23.0×2.5	-20~+70	3.3
CR2330	3	0.2	260	6	20	φ23.0×3.0	-20~+70	4
CR2335	3	0.2	300	6	20	φ23.0×3.5	-20~+70	4.3
CR2354	3	0.4	560	6	20	φ23.0×5.4	-20~+70	6.9
CR2430	3	0.2	270	7	25	φ24.5×3.0	-20~+70	4.5
CR2440	3	0.4	480	7	25	φ24.5×4.0	-20~+70	5.4
CR2450	3	0.4	600	7	25	φ24.5×5.0	-20~+70	6.8
CR2477	3	0.6	1000	7	25	φ24.5×7.7	-20~+70	10.5
CR3032	3	0.4	500	10	30	φ30.0×3.2	-20~+70	6.8
CR3832	3	0.8	850	20	75	φ38.0×3.2	-20~+70	11
CR927	3	0.1	30	1	5	φ9.5×2.7	-20~+70	0.6

お問い合わせは

東機通商株式会社 プロダクトマーケティング部

東京都港区芝5-20-14 三田鈴木ビル4F

☎ 03-3452-9336

contact : [global@toki-com.co.jp](mailto:global@toki-com.co.jp)



東機通商株式会社  
Tokai Denki Tsusho Co., Ltd.