



Model		Dimension (mm)	Weight (g)	Rated Voltage (v)	Rated Capacity (mAh)	Standard Discharge Current (mA)	Max. Current (mA)	
National Standard	International Standard						Continuous	Pulse
<b>High Power Type</b>								
<a href="#"><u>CR14250</u></a>	CR1/2 AA	Ø14.5 x 25.0	10	3	600	5	800	1500
<a href="#"><u>CR14335</u></a>	CR2/3 AA	Ø14.5 x 33.5	14	3	800	5	1000	2000
<a href="#"><u>CR14505</u></a>	AA	Ø14.5 x 50.5	21	3	1400	10	2000	3000
<a href="#"><u>CR15270</u></a>	CR2	Ø15.6 x 27.0	13	3	750	5	1000	2000
<a href="#"><u>CR17250</u></a>	1/2 A	Ø17.0 x 25.0	14	3	750	5	1000	2000
<a href="#"><u>CR17335</u></a>	CR123A	Ø17.0 x 34.5	20	3	1300	10	2000	3000
<a href="#"><u>CR17450</u></a>	-	Ø17.0 x 45.0	26	3	2000	10	2000	3000
<a href="#"><u>CR17505</u></a>	A	Ø17.0 x 50.5	30	3	2200	10	2000	3000
<a href="#"><u>CR18505</u></a>	-	Ø18.5 x 50.5	35	3	2400	10	2000	3000
<a href="#"><u>CR18650</u></a>	-	Ø18.5 x 65.5	45	3	3200	10	2000	3000
<a href="#"><u>CR26500</u></a>	C	Ø26.2 x 50.5	62	3	5000	10	2000	3000
<a href="#"><u>CR34615</u></a>	D	Ø34.0 x 61.5	125	3	10000	10	2000	3000
<a href="#"><u>CR14250SE</u></a>	1/2 AA	Ø14.5 x 25.0	11	3	850	0.5	7	70
<a href="#"><u>CR14335SE</u></a>	2/3 AA	Ø14.5 x 33.5	16	3	1100	1	8	80
<a href="#"><u>CR14505SE</u></a>	AA	Ø14.5 x 50.5	22	3	1800	1	10	100
<a href="#"><u>CR17335SE</u></a>	123A	Ø17.0 x 33.5	22	3	1800	1	10	100
<a href="#"><u>CR17450SE</u></a>	4/5A	Ø17.0 x 45.0	28	<b>3</b>	<b>2400</b>	<b>1</b>	<b>15</b>	<b>150</b>
All products listed above comply with 'UL' Approval								

お問い合わせは  
 東機通商株式会社 プロダクトマーケティング部  
 東京都港区芝5-20-14 三田鈴木ビル4F  
 ☎ 03-3452-9336  
 contact : [global@toki-com.co.jp](mailto:global@toki-com.co.jp)

